



CERTIFICATE NUMBER
EFFECTIVE DATE
EXPIRY DATE
ABS TECHNICAL OFFICE

22-2313849-PDA
06-Dec-2022
05-Dec-2027
London Engineering Department

CERTIFICATE OF Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

ROCKWOOL INTERNATIONAL A/S

located at

HOVEDGADEN 584, , DK-2640 HEDEHUSENE, Denmark

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product: Deck, Class A-30 deck
Model: A30 Deck, Steel SeaRox SL 620 25mm / 25mm
Endorsements:
Tier: 3 - Type Approved, unit certification not required

This Product Design Assessment (PDA) Certificate remains valid until 05/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau Of Shipping

Karthik Subramanian, Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010)

ROCKWOOL INTERNATIONAL A/S

HOVEDGADEN 584

DK-2640 HEDEHUSENE

Denmark

Telephone: +31 475 353915

Fax:

Email: math.mourmans@rockwool.com

Web: www.rockwool-rti.com

Tier: 3 - Type Approved, unit certification not required

Product: Deck, Class A-30 deck
Model: A30 Deck, Steel SeaRox SL 620 25mm / 25mm
Endorsements:

Intended Service:

To form part of A-class fire division (Deck) on ABS Classed Vessels, Mobile Offshore Drilling Units or Facilities

Description:

A30 Deck, Steel with SeaRox SL 620: Composed of steel deck insulated with SeaRox SL 620 (density 100kg/m³) between the stiffeners and SeaRox SL 620 (density 100kg/m³) around the stiffeners. Minimal thickness of the insulation on the deck is 25mm. Minimal thickness of the insulation around the stiffeners is 25mm. Insulation density range on the deck between the stiffeners is 100-130kg/m³ and on the stiffeners 100-130kg/m³. The insulation is fixed to the deck by means of standard 3mm pins in combination with 30-38mm diameter steel clips (spring washers). Distance between pins on stiffeners is maximum 300mm. Distance between pins on the deck (between stiffeners) is maximum 300mm.

For further details about pin-setting and design see drawing 410-1/2/3/4.

Rating:

A-30 Deck

Service Restriction:

- 1) Unit Certification is not required for this product. If the manufacturer or purchaser's request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances must be clearly defined.
- 2) Continuous compliance with the statutory requirements requires maintenance of the Full Type Approval. The scope of Type Approval is to comply with MSC.1/Cir. 1221 dated 1 December 2006.

Comments:

- 1) The Manufacturer has provided a declaration about the control of, or lack of Asbestos in this product.
- 2) Unless specifically directed by the Administration, this approval is not to be construed as a substitute of a flag Administration's approval for the purpose of SOLAS (2014 Consolidated Edition), as amended.
- 3) In those instances where flag administration may have their own specific requirements, flag Administration's approval may be required.

Notes/Drawing/Documentation:

DBI Fire test report ref. PGA10983A, Dated 31 Jan 2017
Insulation installation as per drawing no. 2107004 dated 09 Jan 2017
Pin-setting and design as per drawing 410-1/2/3/4
DBI Assessment Report ref. PHA10909A, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909B, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909C, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909D, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909E, Dated 21 Feb 2017

Terms of Validity:

This Product Design Assessment (PDA) Certificate remains valid until 05/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable

ROCKWOOL INTERNATIONAL A/S

HOVEDGADEN 584

DK-2640 HEDEHUSENE

Denmark

Telephone: +31 475 353915

Fax:

Email: math.mourmans@rockwool.com

Web: www.rockwool-rti.com

Tier: 3 - Type Approved, unit certification not required

Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

ABS Rules for Conditions of Classification 2022: 1-1-4/7.7, 1-1-A3 & A4

ABS Rules for Conditions of Classification - Offshore Units and Structures 2022: 1-1-4/9.7, 1-1-A2 & 1-1-A3

National:

NA

International:

IMO Resolution MSC.307(88) adopted on 3 Dec 2010 - 2010 FTP Code (2012 Edition): International Code for Application of Fire Test Procedures

Government:

NA

EUMED:

NA

OTHERS:

NA



CERTIFICATE NUMBER
EFFECTIVE DATE
EXPIRY DATE
ABS TECHNICAL OFFICE

22-2313849-PDA-DUP
06-Dec-2022
05-Dec-2027
London Engineering Department

CERTIFICATE OF Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

ROXUL ROCKWOOL INSULATION INDIA PVT. LTD.

located at

**PLOT Z/4 DAHEJ SEZ, , DAHEJ, DISTRICT BHARUCH, GUJARAT,
India, 392130**

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product: Deck, Class A-30 deck
Model: A30 Deck, Steel SeaRox SL 620 25mm / 25mm
Endorsements:
Tier: 3 - Type Approved, unit certification not required

This Product Design Assessment (PDA) Certificate remains valid until 05/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau Of Shipping

Karthik Subramanian, Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010)

ROXUL ROCKWOOL INSULATION INDIA PVT. LTD.

PLOT Z/4 DAHEJ SEZ

DAHEJ, DISTRICT BHARUCH GUJARAT

India 392130

Telephone: +91 610835284

Fax:

Email: lukas.Vonsik@rockwool.com

Web: www.rockwool-searox.com

Tier: 3 - Type Approved, unit certification not required

Product: Deck, Class A-30 deck
Model: A30 Deck, Steel SeaRox SL 620 25mm / 25mm
Endorsements:

Intended Service:

To form part of A-class fire division (Deck) on ABS Classed Vessels, Mobile Offshore Drilling Units or Facilities

Description:

A30 Deck, Steel with SeaRox SL 620: Composed of steel deck insulated with SeaRox SL 620 (density 100kg/m³) between the stiffeners and SeaRox SL 620 (density 100kg/m³) around the stiffeners. Minimal thickness of the insulation on the deck is 25mm. Minimal thickness of the insulation around the stiffeners is 25mm. Insulation density range on the deck between the stiffeners is 100-130kg/m³ and on the stiffeners 100-130kg/m³. The insulation is fixed to the deck by means of standard 3mm pins in combination with 30-38mm diameter steel clips (spring washers). Distance between pins on stiffeners is maximum 300mm. Distance between pins on the deck (between stiffeners) is maximum 300mm.

For further details about pin-setting and design see drawing 410-1/2/3/4.

Rating:

A-30 Deck

Service Restriction:

- 1) Unit Certification is not required for this product. If the manufacturer or purchaser's request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances must be clearly defined.
- 2) Continuous compliance with the statutory requirements requires maintenance of the Full Type Approval. The scope of Type Approval is to comply with MSC.1/Cir. 1221 dated 1 December 2006.

Comments:

- 1) The Manufacturer has provided a declaration about the control of, or lack of Asbestos in this product.
- 2) Unless specifically directed by the Administration, this approval is not to be construed as a substitute of a flag Administration's approval for the purpose of SOLAS (2014 Consolidated Edition), as amended.
- 3) In those instances where flag administration may have their own specific requirements, flag Administration's approval may be required.

Notes/Drawing/Documentation:

DBI Fire test report ref. PGA10983A, Dated 31 Jan 2017
Insulation installation as per drawing no. 2107004 dated 09 Jan 2017
Pin-setting and design as per drawing 410-1/2/3/4
DBI Assessment Report ref. PHA10909A, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909B, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909C, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909D, Dated 21 Feb 2017
DBI Assessment Report ref. PHA10909E, Dated 21 Feb 2017

Terms of Validity:

This Product Design Assessment (PDA) Certificate remains valid until 05/Dec/2027 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable

ROXUL ROCKWOOL INSULATION INDIA PVT. LTD.

PLOT Z/4 DAHEJ SEZ

DAHEJ, DISTRICT BHARUCH GUJARAT

India 392130

Telephone: +91 610835284

Fax:

Email: lukas.Vonsik@rockwool.com

Web: www.rockwool-searox.com

Tier: 3 - Type Approved, unit certification not required

Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

ABS Rules for Conditions of Classification 2022: 1-1-4/7.7, 1-1-A3 & A4

ABS Rules for Conditions of Classification - Offshore Units and Structures 2022: 1-1-4/9.7, 1-1-A2 & 1-1-A3

National:

NA

International:

IMO Resolution MSC.307(88) adopted on 3 Dec 2010 - 2010 FTP Code (2012 Edition): International Code for Application of Fire Test Procedures

Government:

NA

EUMED:

NA

OTHERS:

NA